



contrac

CULLEN

6Lpf / 1.6Gpf OR 3Lpf / 0.8Gpf 2PC 17" HIGH ELONGATED DUAL FLUSH

- 4720BIW **Lined Tank**
- 4720BIWU **Unlined Tank**

Product Specs:

- High efficiency dual flush toilet
- 6Lpf / 1.6Gpf or 3Lpf / 0.8Gpf
- Elongated bowl
- Vitreous china
- 17" Bowl height
- White top push actuator
- 12" (305mm) Rough-in
- 1 1/4" Fully glazed ball pass trapway
- 3" Dual flush valve
- Siphon jet flush action
- Water surface (240mm x 165mm) 9 1/2" x 6 1/2"
- Toilet seat not included



Colours To Be Specified:
 Colour: Soft White

Overall Dimensions:

440mm(W) x 750mm(D) x 800mm(H)
 17 1/4"(W) x 29 1/2"(D) x 31 1/2"(H)

Compliance Certifications:

- Meets or exceeds the following:
- IAPMO cUPC
 - US EPA WaterSense
 - ASME A112.19.2 / CSA B45.1-2008
 - ADA ANSI A117.1 Guidelines
 - MaP tested 800g
 - LEED Compliant

Notes:

This toilet is designed to rough-in at a minimum dimension of 305mm (12") from finished wall to C/L of outlet. Supply line not included with fixture and must be ordered separately. Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Products are designed to comply ADA/ANSI A117.1 Standard. It shall be the responsibility of the installer to comply with the local disability codes and standards prior to installing the product.

Shipping:

Cube 6.88
GW 89.23 lbs

