



contrac

CARLTON 1.9Lpf / 0.5Gpf WALL MOUNT URINAL

4810BFX Top Inlet Wall Mount Urinal

Product Specs:

- High efficiency urinal
- 1.9Lpf / 0.5Gpf
- Vitreous china
- Washout flush action
- 3/4" Top inlet spud
- Outlet connection threaded 2" inside NPTF
- Flushing rim
- Extended sides for privacy
- Integral trap
- Elongated 14 3/4" rim from finished wall

Overall Dimensions:

445mm(W) x 375mm(D) x 684mm(H)
17 1/2"(W) x 14 3/4"(D) x 27"(H)

Compliance Certifications:

Meets or exceeds the following:

- IAPMO cUPC
- US EPA WaterSense

Please note: In order to comply with WaterSense certification this urinal must be used with 1.9Lpf / 0.5Gpf WaterSense labeled flushometer.

- ASME A112.19.2 / CSA B45.1-2008
- LEED Compliant

Shipping:

Cube 5.27
GW 65 lbs



Colours To Be Specified:

Colour: Soft White

Notes:

Flush Valve is not included and must be ordered separately. Provide suitable reinforcement for all wall supports. Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Comply ADA Section 4.18 when installed per code.

